



## Analog and Digital Modular Block



Model 2002 and 2000 Dri-Baths



### Choose From Analog and Digital!

- Digital units include built-in temperature sensing probe
- Choose from 1, 2, 3, 4, and 6 block configurations

**Digital Version Includes  
FREE Temperature Probe**

#### Product Description

- Compact design saves valuable bench space.
- Powder-coated steel body construction ensures durability.
- Digital units utilize a PID microprocessor controller with digital temperature set and easy-to-read LED display for accurate and reproducible temperature control.
- Analog units feature a bimetallic dual thermostat control as an economical alternative.



- Dri-baths hold one to six interchangeable modular blocks to accommodate a variety of vessels. Modular blocks sold separately.
- Use Lab-Line brand blocks only.
- Temperature Range: ambient +5°C to 130°C.

#### Analog Units

- Temperature control at 37°C: ±1.5°C.
- Temperature uniformity at 37°C: ±0.5°C.
- Read thermometer and adjust knob controller to your desired setpoint.

#### Digital Units

- Temperature control at 37°C: ±0.1 to 0.2°C.
- Temperature uniformity at 37°C: ±0.1 to 0.4°C.
- Set point is easily adjusted by using up and down arrow keys located on the front of the unit.
- Modular block mounts on a single temperature probe in the bottom of the dri-bath providing better temperature accuracy and control.

### PRODUCT SPECIFICATIONS AND ORDERING INFORMATION

Microprocessor Controlled Dri-Baths - Digital									
Model #	Description	Volts	Electrical (50/60 Hz) Amps	Watts	W	Overall Dimensions Inches (cm)		Shipping Weight Lb. (kg)	US List Price
						H	D		
2000 <sup>1,2</sup>	Single block	120	0.83	100	8.7 (22.1)	3.6 (9)	11.2 (28.4)	5 (2)	\$606.00
2000-1CE <sup>1,4</sup>	Single block	240	0.42	100	8.7 (22.1)	3.6 (9)	11.2 (28.4)	5 (2)	\$606.00
2001 <sup>1,2,3,5</sup>	Double block	120	1.25	150	8.7 (22.1)	3.6 (9)	14.2 (36)	6 (3)	\$804.00
2001-1CE <sup>1,4</sup>	Double block	240	0.63	150	8.7 (22.1)	3.6 (9)	14.2 (36)	6 (3)	\$804.00
2002 <sup>1,2</sup>	Triple block	120	1.67	200	10.8 (27.4)	3.6 (9)	12.0 (30.4)	8 (4)	\$842.00
2002-1CE <sup>1,4</sup>	Triple block	240	0.83	200	10.8 (27.4)	3.6 (9)	12.0 (30.4)	8 (4)	\$842.00
2003 <sup>1,2</sup>	Four block	120	2.5	300	10.8 (27.4)	3.6 (9)	14.1 (35.5)	8 (4)	\$971.00
2003-1CE <sup>1,4</sup>	Four block	240	1.25	300	10.8 (27.4)	3.6 (9)	14.1 (35.5)	8 (4)	\$971.00
2004 <sup>1,2</sup>	Six block	120	3.33	400	10.8 (27.4)	3.6 (9)	17.0 (43.0)	10 (5)	\$1,088.00
2004-1CE <sup>1,4</sup>	Six block	240	1.67	400	10.8 (27.4)	3.6 (9)	17.0 (43.0)	10 (5)	\$1,088.00
Bimetallic Controlled Dri-Baths - Analog									
2050 <sup>1,2,3</sup>	Single block	120	0.83	100	6.2 (16)	3.4 (9)	7.6 (19)	5 (2)	\$266.00
2050-1CE <sup>1,4</sup>	Single block	240	0.42	100	6.2 (16)	3.4 (9)	7.6 (19)	5 (2)	\$266.00
2052 <sup>1,2,3</sup>	Double block	120	1.25	150	8.4 (21)	3.4 (9)	8.6 (22)	6 (3)	\$476.00
2052-1CE <sup>1,4</sup>	Double block	240	0.63	150	8.4 (21)	3.4 (9)	8.6 (22)	6 (3)	\$476.00
2053 <sup>1,2,3</sup>	Triple block	120	1.67	200	11.25 (29)	3.4 (9)	9.1 (23)	8 (4)	\$647.00
2053-1CE <sup>1,4</sup>	Triple block	240	0.83	200	11.25 (29)	3.4 (9)	9.1 (23)	8 (4)	\$647.00
2054 <sup>1,2,3</sup>	Four block	120	2.50	300	8.3 (21)	3.4 (9)	12.4 (31)	8 (4)	\$713.00
2054-1CE <sup>1,4</sup>	Four block	240	1.25	300	8.3 (21)	3.4 (9)	12.4 (31)	8 (4)	\$713.00
2056 <sup>1,2,3</sup>	Six block	120	3.33	400	11.25 (29)	3.4 (9)	12.9 (33)	10 (5)	\$917.00
2056-1CE <sup>1,4</sup>	Six block	240	1.67	400	11.25 (29)	3.4 (9)	12.9 (33)	10 (5)	\$917.00

<sup>1</sup> ETL, <sup>2</sup> CSA, <sup>3</sup> UL, <sup>4</sup> CE, <sup>5</sup> CUL

All models include heavy duty 3-wire line cord and block puller; 120 volt models include plug.