

## Thermolyne Hot Plate and Hot Plate Stirrers



# Aluminum Top Hot Plates



Type HP88700

## Uniform Heating and Rugged Construction!

- Low temperature control
- Uniform heating

### Product Description

- Thermostatic control provides excellent temperature stability.
- Maintains temperature stability of  $\pm 3^{\circ}\text{C}$  ( $\pm 5^{\circ}\text{F}$ ).
- Provides reliable control at low temperatures for warming applications and quick heat-up for bringing aqueous solutions to a boil in 15-18 minutes.
- Temperature uniformity at maximum temperature is  $\pm 8^{\circ}\text{C}$  ( $\pm 14^{\circ}\text{F}$ ).
- Top side drip edge channels spilled liquid away from knobs and provides protection for inside components.

- All units include a power indicator light for safety.
- Not recommended for use with metal vessels or sand baths.
- Accommodates up to 25 lb (11.3 kg) loads.

### Application

- Warming/curing applications - pastes, adhesives, and solder

### PRODUCT SPECIFICATIONS

Type	Heating Surface Inches (cm)		Overall Dimensions Inches (cm)			Shipping Weight Lb. (kg)
	W	D	W	H	D	
HP88700	7 (17.7)	7 (17.7)	9 (22.9)	5 (12.7)	9.6 (24.4)	9 (4.1)

### ORDERING INFORMATION

Model #	Volts	Electrical (50/60 Hertz)		Operating Temp Range		US List Price
		Amps	Watts	$^{\circ}\text{C}$	$^{\circ}\text{F}$	
HP88725	120	7.0	840	40-370	104-698	\$264.00
HP88720-26	220-240	3.6	840	40-370	104-698	\$264.00

-26 Models Supplied with European cord set.

### ACCESSORIES

Model #	Description	US List Price
SH1070X2	Workstation	\$96.00