



"Y" Connectors

Autoclavable. Polypropylene.

12 per bag, 6 bags per case.



CATALOG NO.	TUBING I.D.	PRICE/BAG
F19612-0000	3.2mm (1/8")	\$14.50
F19613-0000	4.7mm (3/16")	14.50
F19614-0000	6.0mm (1/4")	14.50
F19615-0000	8.0mm (5/16")	14.50
F19616-0000	9.5mm (3/8")	15.75
F19618-0000	12.7mm (1/2")	20.75



"T" Connectors

Polypropylene. Autoclavable.

12 per bag, 6 bags per case.



CATALOG NO.	TUBING I.D.	PRICE/BAG
F19603-0000	4.7mm (3/16")	\$14.75
F19604-0000	6mm (1/4")	14.50
F19606-0000	9.5mm (3/8")	16.00



Check Valves

Stops Reverse Flow of Liquid When Pressure is Interrupted

Useful when connecting a vacuum line to a filter flask. Polypropylene valve with neoprene valve disk. Recommended maximum pressure 20psi (1034 Torr). Autoclavable. **6 per bag, 12 bags per case.**



CATALOG NO.	OVERALL LENGTH	LENGTH TAPERED END	DIAMETER TAPERED END IN	DIAMETER TAPERED END OUT	PRICE/BAG
H19715-0000	60mm (2 1/2")	19mm (3/4")	3.1 to 6.4mm (1/8 to 1/4")	3.1 to 6.4mm (1/8 to 1/4")	\$29.40
H19716-0000	60mm (2 1/2")	19mm (3/4")	6.4 to 9.5mm (1/4 to 3/8")	6.4 to 9.5mm (1/4 to 3/8")	29.40
H19717-0000	76mm (3")	25mm (1")	9.5 to 12.7mm (3/8 to 1/2")	9.5 to 12.7mm (3/8 to 1/2")	29.40

Great For Vacuum Lines in Filtration



Needle Valve

Precise Flow

Teflon® PTFE needle valve is ideal for use with corrosives, because fluids come into contact with only glass and Teflon®. Excellent for use as replacement stopcocks in

vacuum systems. 2mm I.D. optional removable glass arms for tubing connections, Available on Special Order.



CATALOG NO.	DESCRIPTION	PRICE/EACH
H30849-0000	Needle valve only	\$99.90



Stopcocks

2-Way and 3-Way Connections

With a removable leak-proof plug made of chemical-resistant, non-stick Teflon® PTFE, these

polypropylene stopcocks have serrated tubulations that accept 6.4mm to 9.5mm (1/4" to 3/8") I.D. tubing. 3-way models allow connection of any two or all three arms. Pressure rating is 240 KPa (35 psi). **Per each, 6 per case.**



CATALOG NO.	DESCRIPTION	BORE SIZE	PRICE/EACH
F30890-0000	2-way	2mm	\$23.85
F30891-0000	2-way	4mm	22.40
F30894-0000	3-way	2mm	27.00
F30895-0000	3-way	4mm	27.00



Stopcocks

2 Piece Design Needs No Lubrication

Two piece molded polyethylene stopcock. Parts snap together forming a tight seal, and the free-turning key needs no lubrication. A quarter turn shuts off flow. Maximum pressure rating 48 KPa (7 psi), 50cm of water.



CATALOG NO.	DESCRIPTION	PRICE/EACH
F30915-0000	Length 70mm (2 3/4"), fits tubing 9.5mm (3/8") I.D.	\$10.00
F30917-0000	Length 98mm (3 7/8"), fits tubing 12.7mm (1/2") I.D.	12.65

Instant Cut Off Control

Stopcocks

Chemical Resistant Fluoroplastic

PVDF (polyvinylidene fluoride) is a fluoroplastic resistant to most chemicals and withstands temperatures up to 204°C (400°F). Serrated tubulations accept rubber or plastic tubing. 3-way configuration permit connection of any two or all three ports. Maximum pressure rating 34.3 KPa (5 psi).



CATALOG NO.	DESCRIPTION	BORE SIZE	ACCEPTS TUBING I.D.	PRICE/EACH
F30888-0006	3-way	4mm	6mm	\$58.00
F30888-0008	3-way	6mm	8mm	66.00
F30888-0010	3-way	8mm	10mm	74.50

Bobbitt Valve

Easy to Install and Simple to Operate

Outfitted with a convenient on/off valve for use in dispensing from aspirator bottles. Just squeeze and hold the soft center of the valve to begin flow; release it to suspend flow. Made of silicone rubber and polypropylene, the internal surfaces are coated with a fluorocarbon resin for maximum chemical resistance. Steam autoclavable at 121°C (250°F). **Per each, 4 per case.**



CATALOG NO.	FITS TUBING I.D.	PRICE/EACH
F30848-0004	6 to 8mm (1/4 to 5/16")	\$32.75

For Easy, Neat Dispensing