



Small Bore Teflon® PTFE Tubing

Minimum cut 25ft.



CATALOG NO.	I.D.	WALL	PRICE/FOOT
H21195-0034	.86mm (.034)	.30mm (.012)	\$1.29
H21195-0038	.97mm (.038)	.30mm (.012)	1.29
H21195-0047	1.19mm (.047)	.30mm (.012)	1.29
H21195-0068	1.73mm (.068)	.30mm (.012)	1.50



Plastic Tubing Cutter

Pocket-Sized Cutter

The portable, pocket-sized cutter cuts flexible tubing from 1.6mm to 19mm (1/16 to 3/4") O.D. The jaw is lightly spring-loaded and closes automatically for safety. The hardened steel blade, which is replaceable, makes clean, straight cuts. 76mm (3") long.

CATALOG NO.	DESCRIPTION	CASE	PRICE/EACH
H21010-0000	Plastic Tubing Cutter	12	\$13.95
H21011-0000	Replacement Blades.	24	5.70



Metric Diameter Gauge Tubing Sizer

Stop Guessing... Know What Size You Need

A handy metric diameter gauge that will end doubt about inside or outside diameters. The gauge measures glass and plastic tubing, connecting pieces, rods, test tubes, etc. between 1.5 and 16mm. Holes on one side measure O.D.; pins on the other side measure I.D. Keep one with your tubing and one with your culture, centrifuge or test tubes. Made of polypropylene, the gauge is autoclavable.

polypropylene, the gauge is autoclavable.



CATALOG NO.	WIDTH X LENGTH X HEIGHT	PRICE/EACH
F13390-0000	5 x 12 x 1.2cm (2 x 4 3/4 x 1/2")	\$16.50



Tubing Holder

Clips on Beakers and Pitchers

Hold flexible tubing steady in beakers or pitchers with this polypropylene clip. It fits securely onto the edge and has a 51mm (2") long arm with a hole that will accept tubing up to 9.5 mm (3/8") O.D. Autoclavable. **6 per bag, 6 bags per case.**



CATALOG NO.	PRICE/BAG
F18235-0000	\$12.00

Tubing Sinkers-PTFE

Keep Tubing from Adhering to Container Wall

Teflon® sinkers keep tubing at the bottom of your container. Ideal for use with pumps and dispensers, these sinkers have hose barb ends for simple tubing connection. Solvent resistant and autoclavable. Sold as set of two sizes or one each.



CATALOG NO.	FITS TUBING SIZE I.D.	PRICE
F32903-0100	one of each size	\$28.50/Set
F32903-0102	5.5 to 6.2mm (1/8 to 1/4")	13.00/Each
F32903-0104	8 to 10.5mm (5/16 to 3/8")	19.50/Each

Stat-O-Lok™ Disconnects

Quick-disconnect in-line tubing connectors. Use Stat-O-Lok™ connectors for no mess tubing hook-ups. These chrome plated brass connectors feature easy to use slide locks for leak-free



in-line connections and automatic shut off when disconnected. Hose barb ends accept flexible tubing. Operate at temperatures to 82°C (180°F), pressures to 1.7 Mpa (250 psi), vacuum to 30 microns of Hg. Chrome plated valves provide dependable operation; ideal for liquid and gas connectors in biomedical instrumentation and general industrial applications.

CATALOG NO.	FITS TUBING I.D.	COUPLING TYPE	PRICE/EACH
F19723-0202	3mm (1/8")	male	\$23.00
F19723-0802	3mm (1/8")	female	33.50
F19724-0204	6mm (1/4")	male	23.95
F19724-0804	6mm (1/4")	female	35.00

FAUCETS

Faucet

Same 12.7mm bore (1/2") needle type, polyethylene faucet with same Teflon® O-ring as the F30852 but with the addition of a male threaded outlet. The outlet, made of polyethylene, accommodates standard 19mm x 292mm (3/4 x 11 1/2") threads per inch garden hose coupling. **Per each, 12 per case.**



CATALOG NO.	DESCRIPTION	PRICE/EACH
H30857-0000	19mm (3/4") NPT	\$30.00

Heavy Duty Faucets

Needle type, Teflon® O-ring seal inside polyethylene faucet prevents back pressure liquid from escaping through the operating knob. Used on Scienceware® aspirator bottles and tanks. The outlet accepts 16mm I.D. (5/8") tubing. The F30852 fits standard steel drums **Per each, 12 per case.**



CATALOG NO.	DESCRIPTION	PRICE/EACH
F30851-0000	12.7mm (1/2") NPT	\$26.00
F30852-0000	19mm (3/4") NPT	26.00